

Coltri/Nuvair Mini Tech

The Mini Tech is our go to Compressor set up for a wide variety of applications in both breathing air and industrial air use. Compact design and fold away handles make for easy lifting and portability of the compressor. On board Grade E air purification insures breathing air quality standards. A wide variety of customized options to meet individual needs are noted on the options list below. If portability and dependability are top on your list, this is the compressor for you.

Features

- 5000 PSI Max Pressure
- Industrial Air Filtration
- 2 Fill Whips
- Electric or Honda Gas or Diesel Motor
- Stainless Steel Intercoolers
- 4 Lifting Handles
- All important parts are protected inside frame
- Superior Vibration Isolation



pictured with multiple options

stainless frame option

Options

- Motor Starter/Electric Start
- Automatic Condensate Drains
- Pressure Switch
- Hour Meter
- High Temp Shut Down
- Low Oil Shut Down
- Interstage Pressure Gauges
- Visual Moisture Indicator
- Stainless Frame

Model	MCH13 / 7 Mini Tech	MCH16 / 9 Mini Tech
Filling Time*	Approx. 9 Minutes	Approx. 7.4 Minutes
Cubic Feet/Minute	7.6 FAD 8.9 SCFM*	9.4 FAD 10.8 SCFM*
Liters/Minute	215 FAD	265 FAD
Motor Options	Single or Three Phase	Single or Three Phase
230 V - E1 - 50 or 60 Hz	25 Amp 5.5 hp (4 kW) (Part# 8040.1)**	34 Amp 7.5 hp (5.5 kw) (Part# 8037.1)**
230 V - E3 - 50 or 60 Hz	14 Amp 5.5 hp (4 kW) (Part# 8040.2)**	20 Amp 7.5 hp (5.5 kw) (Part# 8037.2)**
440 V - E3 - 50 or 60 Hz	7 Amp 5.5 hp (4 kW) (Part# 8040.3)**	10 Amp 7.5 hp (5.5 kw) (Part# 8037.3)**
Honda Gas	6.5 hp (4.1 kW) (Part# 8039)	9 hp (6.6 kW) (Part# 8038)
Yanmar Diesel	N/A	10 hp (7.5kW) (Part# 8038-DY)
Kohler Diesel	N/A	10 hp (7.5kW) (Part# 8038-DL)
Max Operating Pressure	5000 PSI (345 Bar)	5000 PSI (345 Bar)
RPM	1350	1550
Number of Stages	3	3
Number of Fill Hoses	2	2
Condensate Drain	Manual	Manual
Sound Level @ 3 Meters	81 dB	80-96 dB
Dimensions: (H x W x D)	24 in x 45 in x 22 in (61 x 114 x 56 cm)	
Weight	320-421 lbs (145-191 kg)	
Lubrication	Splash Lubrication, capacity 1.6 qts.	

* Single 80 Cu.. Ft. cylinder from 500 to 3000 PSI

** Part number reflects 60Hz Model. Inquire about 50 Hz Model