

## 3111 TWO-WAY SPEAKER WITH CALL SWITCH

### DESCRIPTION

The Amron International Model 3111 Two-Way Speaker with Call Switch provides chamber to dive control communication.

Two-way speaker, call switch, and chamber to Dive Control (DC). Headset jack wired for conference style communications (duplex). Speaker is 15 Watts, 8 ohm.

Optional headset permits conversation without disturbing other chamber occupants. Individual connections for headset and speaker allow DC to continue chamber monitoring while communicating with a person using the headset.

A Push-to-Call switch activates a call indicator on the Amron Comm Routing Panel (CRP). The CRP activates an audio alarm and a visual indicator identifying the caller's location. Housing is die cast zinc with gray epoxy powdercoat.

### OVERVIEW

#### Features:

- 8 Ohm
- 15 Watts speaker
- Housing is die cast zinc with gray powder coat with 300 series stainless steel front panel.

#### Dimensions:

- Height: 5.5 in. (14 cm)
- Width: 5.5 in. (14 cm)
- Depth: 4 in. (10.2 cm)
- Weight: 5 lbs. (2.3 kg)

#### Includes:

- 7 Pin MS Connector - P/N: MS-3106A-16S-1S
- MS Cable Clamp 16S-1 - P/N: MS-3057-8A



**DISCLAIMER NOTICE:** Amron's chamber communications are designed to be used in air chambers where oxygen concentrations remain below 23.5%. Our communications products (including communicators, speakers, entertainment systems, and other communications accessory items) are NOT designed for oxygen service, are not intrinsically safe, and do not meet the criteria given in NFPA-99, Chapter 20 and other applicable definitions. Misuse of our chamber communicator products in high-concentration Oxygen environments may result in serious injury and/or death.

## 3111 TWO-WAY SPEAKER WITH CALL SWITCH

### MOUNTING AND ELECTRICAL DIAGRAM

