



Snooperette Options-

You can customize your new BIRNS SNOOPERETTE, often at no extra cost, to make it ideal for your own requirements. These options are:

• <u>Lamp:</u>	Many different lamps are available for the SNOOPERETTE. Please see the Lamp Options table 'A' below for details of the most popular choices.
• <u>Lens:</u>	Six different lenses are available for different applications. Please see the Lens Options Table 'B' below for details.
• <u>Mount:</u>	Various mounting options are available for different applications. Please see the Mount Options table 'C' below for details.

Lamp Options Table 'A'	Notes:																																																																		
	1. Unless specified otherwise, the default "standard" lamp installed in the SNOOPERETTE is 32C-003 (12v/100w)																																																																		
	2. These are the most popular lamp choices, but many others are available for special applications. Ask our Technical Sales Team for more information.																																																																		
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Lamp Part No.</th> <th style="text-align: center;">Volts</th> <th style="text-align: center;">Watts</th> <th style="text-align: center;">Color (K)</th> <th style="text-align: center;">Output</th> <th style="text-align: center;">Rated Life (Hours)</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">32C-001</td> <td style="text-align: center;">12</td> <td style="text-align: center;">25</td> <td style="text-align: center;">2,925</td> <td style="text-align: center;">260 lumens</td> <td style="text-align: center;">3,000</td> </tr> <tr> <td style="text-align: center;">32C-002</td> <td style="text-align: center;">12</td> <td style="text-align: center;">50</td> <td style="text-align: center;">3,050</td> <td style="text-align: center;">895 lumens</td> <td style="text-align: center;">3,000</td> </tr> <tr> <td style="text-align: center;">32C-003</td> <td style="text-align: center;">12</td> <td style="text-align: center;">100</td> <td style="text-align: center;">3,350</td> <td style="text-align: center;">N/A</td> <td style="text-align: center;">200</td> </tr> <tr> <td style="text-align: center;">32C-024</td> <td style="text-align: center;">24</td> <td style="text-align: center;">20</td> <td style="text-align: center;">2,900</td> <td style="text-align: center;">600 lumens</td> <td style="text-align: center;">2,500</td> </tr> <tr> <td style="text-align: center;">32C-027</td> <td style="text-align: center;">24</td> <td style="text-align: center;">50</td> <td style="text-align: center;">2,950</td> <td style="text-align: center;">2,900 cd</td> <td style="text-align: center;">4,000</td> </tr> <tr> <td style="text-align: center;">32C-026</td> <td style="text-align: center;">24</td> <td style="text-align: center;">75</td> <td style="text-align: center;">2,900</td> <td style="text-align: center;">2,500 cd</td> <td style="text-align: center;">3,000</td> </tr> <tr> <td style="text-align: center;">32C-004</td> <td style="text-align: center;">24</td> <td style="text-align: center;">200</td> <td style="text-align: center;">3,400</td> <td style="text-align: center;">N/A</td> <td style="text-align: center;">50</td> </tr> <tr> <td style="text-align: center;">32C-005</td> <td style="text-align: center;">24</td> <td style="text-align: center;">250</td> <td style="text-align: center;">3,400</td> <td style="text-align: center;">N/A</td> <td style="text-align: center;">50</td> </tr> <tr> <td style="text-align: center;">32C-015</td> <td style="text-align: center;">30</td> <td style="text-align: center;">50</td> <td style="text-align: center;">3,450</td> <td style="text-align: center;">N/A</td> <td style="text-align: center;">25</td> </tr> <tr> <td style="text-align: center;">32C-006</td> <td style="text-align: center;">30</td> <td style="text-align: center;">80</td> <td style="text-align: center;">3,400</td> <td style="text-align: center;">N/A</td> <td style="text-align: center;">15</td> </tr> </tbody> </table>	Lamp Part No.	Volts	Watts	Color (K)	Output	Rated Life (Hours)	32C-001	12	25	2,925	260 lumens	3,000	32C-002	12	50	3,050	895 lumens	3,000	32C-003	12	100	3,350	N/A	200	32C-024	24	20	2,900	600 lumens	2,500	32C-027	24	50	2,950	2,900 cd	4,000	32C-026	24	75	2,900	2,500 cd	3,000	32C-004	24	200	3,400	N/A	50	32C-005	24	250	3,400	N/A	50	32C-015	30	50	3,450	N/A	25	32C-006	30	80	3,400	N/A	15
Lamp Part No.	Volts	Watts	Color (K)	Output	Rated Life (Hours)																																																														
32C-001	12	25	2,925	260 lumens	3,000																																																														
32C-002	12	50	3,050	895 lumens	3,000																																																														
32C-003	12	100	3,350	N/A	200																																																														
32C-024	24	20	2,900	600 lumens	2,500																																																														
32C-027	24	50	2,950	2,900 cd	4,000																																																														
32C-026	24	75	2,900	2,500 cd	3,000																																																														
32C-004	24	200	3,400	N/A	50																																																														
32C-005	24	250	3,400	N/A	50																																																														
32C-015	30	50	3,450	N/A	25																																																														
32C-006	30	80	3,400	N/A	15																																																														
Lens Options Table 'B'	Changing the lens is very quick and simple, so it's easy to keep various lenses on hand for different jobs.																																																																		



Lens	Part No.	Benefit	Application
Clear	35A-007	Greatest light output	General illumination
Clear, Deep	35A-008	Greatest light output	General illumination; deep-submergence
Frosted	35A-009	Diffuses light beam	Excellent for video or film
Frosted, Deep	35A-010	Diffuses light beam	Video or film; deep-submergence
Blue	35A-011	Matches color temperature of daylight (5000 K)	Reduces backscatter in murky water; good for color filming
Blue-Frosted	35A-012	Diffuses light output and increases color to 5000 K	Excellent for color filming, or for filming or videotaping in murky water

Mount Options Table 'C'	Changing the mount is very quick and simple, so it's easy to keep various mounts on hand for different jobs.
--------------------------------	--------------------------------------------------------------------------------------------------------------

Mount	Part No.	Application
Stainless Steel Yoke Assembly	44A-006	General purpose yoke-mounting
Handgrip Assembly	44B-001	Hand-held; leaves hand available for work
Helmet Mount, Superlite	44C-003	Excellent for helmet mounting on Kirby-Morgan/DSI's Superlite